






# PIÑONES PARA TAPER BUSHES WITH HARDENED TEETH

## SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH

**3/8" x 7/32"**

9,525 x 5,72 mm  
Rodillo 6,35 mm  
06B - 1

B1	C	r3
5,3	1	10



Material acero C45




Z	de	dp	dm	simple taper		Kg.
				A		
17	55,5	51,83	45	22	1008	0,11
19	61,6	57,86	45	22	1008	0,15
21	67,6	63,90	46	22	1008	0,18
23	73,7	69,95	63	25	1210	0,27
25	79,7	75,99	63	25	1210	0,32

Z	de	dp	dm	simple taper		Kg.
				A		
27	85,7	82,04	63	25	1210	0,34
30	94,8	91,12	63	25	1210	0,39

**1/2" x 5/16"**

12,7 x 7,75 mm  
Rodillo 8,51 mm  
08B - 1

B1	C	r3
7,2	1,3	13



Material acero C45




Z	de	dp	dm	simple taper		Kg.
				A		
15	66,5	61,80	45	22	1008	0,16
17	74,5	69,11	60	25	1210	0,22
19	82,5	77,15	63	25	1210	0,33
21	90,6	85,21	71	25	1610	0,36
23	98,7	93,26	76	25	1610	0,50

Z	de	dp	dm	simple taper		Kg.
				A		
25	106,7	101,32	76	25	1610	0,56
27	114,8	109,39	76	25	1610	0,63
30	126,9	121,49	90	32	2012	0,91

**5/8" x 3/8"**

15,875 x 9,65 mm  
Rodillo 10,16 mm  
10B - 1

B1	C	r3
9,1	1,6	16



Material acero C45

Z	de	dp	dm	simple taper		Kg.
				A		
13	73,2	66,33	47	22	1008	0,23
15	83,2	76,35	60	25	1210	0,30
17	93,3	86,39	71	25	1610	0,38
19	103,3	96,44	75	25	1610	0,54
21	113,4	106,51	76	25	1610	0,65

Z	de	dp	dm	simple taper		Kg.
				A		
23	123,5	116,58	76	25	1610	0,77
25	133,6	126,66	90	32	2012	1,05
27	143,6	136,74	90	32	2012	1,17
30	158,8	151,87	90	32	2012	1,40



# PIÑONES PARA TAPER TEMPLADOS POR INDUCCION - DIN 8187 - ISO 606

## SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH




**3/4" x 7/16"**

19,05 x 11,68 mm  
Rodillo 12,07 mm  
12B - 1

B1	C	r3
11,1	2	19

Material acero C45

Z	de	dp	dm	simple taper		Kg.
				A	taper	
13	87,8	79,60	60	25	1210	0,35
15	99,8	91,62	70	25	1610	0,44
17	111,9	103,67	76	25	1610	0,66
19	123,9	115,73	90	32	2012	0,94
21	136,0	127,81	102	44	2517	1,24






**1" x 17,02 mm**

25,4 x 17,02 mm  
Rodillo 15,88 mm  
16B - 1

B1	C	r3
16,2	2,5	26

Material acero C45

Z	de	dp	dm	simple taper		Kg.
				A	taper	
15	133,7	122,16	76	38	1615	1,30
17	149,8	138,23	90	32	2012	1,59
19	165,9	154,31	108	44	2517	2,29
21	182,0	170,42	110	44	2517	2,81
23	198,1	186,53	110	44	2517	3,38



**1"1/4 x 3/4"**

31,75 x 19,56 mm  
Rodillo 19,05 mm  
20B - 1

B1	C	r3
18,5	3,5	32

Material acero C45

Z	de	dp	dm	simple taper		Kg.
				A	taper	
15	167,7	152,72	110	44	2517	3,39
17	187,7	172,78	110	44	2517	5,07
19	207,9	192,91	110	44	2517	6,75
21	228,0	213,04	120	44	2517	7,70
23	248,2	233,17	120	44	2517	8,78

